



HYDROGEN DETECTION, LEAK LOCATION AND ANALYSER SOLUTIONS

FIXED HYDROGEN GAS SENSORS: FIXaHY SERIES

MODEL: FIXaHY-G-02-03060102103010

APPLICATION: HYDROGEN SAFETY IN POWER GENERATION PLANTS



Widest Range of Parametric Selection Available For

Operating Range | Resolution | Sensitivity | Response Time | Sensor Size | Sensor Output | Enclosure Type
Hazardous & Non-Hazardous Area Compliant | Ingress Protection IP 65 to IP 68 | Process Analysis

Bespoke Customized Solution Development

Our high-class R&D Lab and Calibration + Repair facility can cater to most challenging requirements

Manufactured By: Multi Nano Sense Technologies Private Limited

RO: RH 14, Swapnil Enclave, Amravati Road, Kachimet, Nagpur, India - 440023

R&D: Block 324, First Floor, Sheela Complex, Amravati Road, Wadi, Nagpur, India - 440023

M: +91 99205 63787 | W: www.multinanosense.com | CIN: U74999MH2017PTC293374

General Description

FIXaHY-G-02-03060102103010 is a robust Hydrogen Gas Sensor with ultra-high sensitivity to even 10 PPM (part per million) over a very wide range up to 5% H₂ v/v in Air. **FIXaHY-G-02-03060102103010** is based on our Patented Solid State Electrochemical Sensor Technology with Solid Electrolyte and Novel Reference Electrode. It measures direct partial pressure of Hydrogen in Air. It is specific, selective, and intelligent to Hydrogen alone and does not face any interference from other combustible and reducing gases, unlike other technologies used for generic Hydrogen detection. These are vast improvements in bridging the gaps in Hydrogen sensing requirement.

Application Description

FIXaHY-G-02-03060102103010 is used for area monitoring in power generation plants to protect the plant from Hydrogen explosions by continuously monitoring the concentration of Hydrogen and raising alarms if Hydrogen concentration crosses the user defined thresholds. It is the most capable sensor technology for critical applications where 100% pure Hydrogen is stored, transported, and transacted. The sensor does not get damaged upon exposure to high concentrations of H₂ and had an operating life of 5 years. The sensor is housed in a robust waterproof and dust-proof IP 68 aluminum enclosure for withstanding tough environmental conditions and ensuring a long sensor life.

FIXaHY-G-02-03060102103010 provides a linear output of 0V to 5V over the entire range and can be integrated with our single or multi-channel Control & Display Units for local display, trigger-based automation, local alarms, calibration, data logging and system settings.

Key Advantages

- **Small Form Factor:** The entire sensing system is housed in a 75x80x57 mm enclosure.
- **Fastest response time:** Instantaneous response with maximum lag of 3 seconds.
- **No damage on over-exposure:** Even if sensor is momentarily exposed to 100% pure Hydrogen.
- **No Cross Sensitivity:** Other combustible and reducing gases do not interfere with sensor functioning.
- **No False Alarms:** Highly reliable operation due to selective sensing of Hydrogen alone.
- **Very Fast Recovery:** Immediate feedback of Hydrogen concentration reduction due to response action.
- **Very Sensitive:** Core composition of sensing elements is tailor made to suit detection as low as 1 ppm.
- **High Resolution:** Intricate and high precision electronics ensure 10 ppm resolution over entire range.
- **Long Life:** Capex cost is spread over 5 years.
- **User Friendly Calibration & Comprehensive AMC Option:** Low cost and low hassle after sales service.
- **End to End Support:** Remote as well as on-site support. Deep evaluation studies in R&D facility.
- **Robust Enclosure:** Best in class Ingress Protection IP 68 for weatherproof and waterproof deployment.
- **Expert Consultancy:** Our seasoned engineers can guide you for ideal product selection from our vast range of options to suit your requirements.



Manufactured By: Multi Nano Sense Technologies Private Limited

RO: RH 14, Swapnil Enclave, Amravati Road, Kachimet, Nagpur, India - 440023

R&D: Block 324, First Floor, Sheela Complex, Amravati Road, Wadi, Nagpur, India - 440023

M: +91 99205 63787 | W: www.multinanosense.com | CIN: U74999MH2017PTC293374

Technical Specifications

FIXED HYDROGEN GAS SENSOR – FIXaHY-G-02-03060102103010		
Sr. No.	Parameters	Description
1	Sensor Technology	Solid State Electrochemical Cell (Direct Partial Pressure Measurement of Hydrogen in gaseous Fluid based on Proprietary Indian Patent No. 252998)
2	Range	0% to 5% H₂ v/v in Air. Output Signal is 0V to 5V DC. Ambient: 0.5V (±5mV), 5% H ₂ v/v in Air = 4.5V(±5mV). Smart fault indication and over-range indication
3	Initial Response Time	Instantaneous, less than 3 seconds
4	Cross sensitivity	Nil Cross-Sensitivity. Specific & selective only to Hydrogen with no interference from other combustible, reducing or inert gases.
5	Accuracy	± 5 % of indicated reading.
6	Operating Temperature	0°C to +55°C
7	Humidity	98% RH at 40°C Non-condensing
8	Transducer	4 Wires containing sensor and Pre-amplifier, Protruding 10mm outside from enclosure facia 28Ø Diameter
9	External Power required	9Vdc to 15Vdc, 15mA max.
10	Dimensions and weight	Dimensions - 75x80x57 mm (L x W x D) and Weight - 500 grams
11	Sampling	By Diffusion, Gas aperture Ø 4mm
12	Housing Material	Aluminium (Die Cast). Ingress Protection IP 68
13	Max O/P current loading	<= 0.5 mA
14	Compatible Interfaces	MNST's proprietary Control & Display Units and other user interface like PLC/DCS/BMS etc which can accept analogue voltage output (0V to 5V)
15	Connectivity	4 or 6-pin round circular connector (male) at one end, 4-core (Shielded (SPC) 6 - 8 mm cable and interface-compatible connector at another end.
16	Mounting	Wall mounting using brackets supplied along with detector. Head room minimum 90mm.
17	Calibration Frequency	Recommended for high accuracy: Once in every 6 months Minimum: Once in every 12 months
18	Over-exposure Damage Resistant	The sensor does not get damaged upon momentary over-exposure to very high concentration of Hydrogen. The output signal/ readout on the control unit shall saturate at full scale if exposure is above the pre-defined full scale of the sensor. The sensor shall resume normal functionality once Hydrogen level drops. The sensor may take longer time to recover and come out of saturation after prolonged over-exposure if exposed for more than 30 to 60 seconds.
19	Standard Warranty	The goods shall be warranted against issues arising out of manufacturing and workmanship defects for a period of 12 months from date of acceptance of goods at site or 18 months from the date of invoice. It shall not cover physical damage, or any improper functioning caused due to User's negligence or such use in contravention of the guidelines described in the User's Manual supplied along with the product. Warranty does not cover calibration or AMC of sensor. A warranty certificate shall be issued, containing all terms and conditions.
20	Extended Warranty	Similar coverage as Standard Warranty. Can be purchased as an add-on for 2/3/4 years in addition to standard warranty.

Manufactured By: Multi Nano Sense Technologies Private Limited

RO: RH 14, Swapnil Enclave, Amravati Road, Kachimet, Nagpur, India - 440023

R&D: Block 324, First Floor, Sheela Complex, Amravati Road, Wadi, Nagpur, India - 440023

M: +91 99205 63787 | W: www.multinanosense.com | CIN: U74999MH2017PTC293374



MULTI NANO SENSE TECHNOLOGIES PVT LTD
FIXED HYDROGEN GAS SENSOR
MODEL: FIXaHY-G-02-03060102103010

Contact Us

Do not hesitate to give us a call or write to us for detailed discussion, enquiries, assistance, feedback, or suggestions. Our team will be glad to help you out.

Single Point of Contact

For Collaborations
For Enquiries
For Technical Assistance
For Feedback and Suggestions

M: +91 99205 63787

E: collaborations@multinanosense.com
E: sales@multinanosense.com
E: techassist@multinanosense.com
E: feedback@multinanosense.com

Do visit our website for more information and upcoming technologies -----> www.multinanosense.com

Thank You for showing interest in our products and services!

Technical specifications are subject to change without prior notice, due to continuous R&D and development of Company's Products.

Manufactured By: Multi Nano Sense Technologies Private Limited

RO: RH 14, Swapnil Enclave, Amravati Road, Kachimet, Nagpur, India - 440023
R&D: Block 324, First Floor, Sheela Complex, Amravati Road, Wadi, Nagpur, India - 440023
M: +91 99205 63787 | W: www.multinanosense.com | CIN: U74999MH2017PTC293374